

Mini leak sealing bags



- Quickly attached with Velcro belt
- Delivered in practical case
- Up to 1.4 bar (20.3 psi) counterpressure
- For containers with diameters 10 – 90 cm (4 – 35 inch)

The small and quick leak-stoppers.

Vetter mini leak sealing bags are ideal for leaks in small containers with a diameter between 10 and 90 cm (4 and 35 inch). The mini leak sealing bags securely seal liquids and gases, are easy to attach and provide a quick solution in emergencies. The maximum working pressure of 1.5 bar (21.75 psi) is soon reached with just a few strokes of the foot pump - and the container is sealed. Quick and safe Velcro fasteners on the metal-free tension belts make light work of attaching the sealing bags - even in difficult positions.

Technical Data

Uniform sealing pressure of 14 m WC (20.3 psi).

- Working pressure: 1.5 bar (21.75 psi)
- Test pressure: 1.95 bar (28.5 psi)

* around valve + 6 mm (0.2 inch)

Product	Art.-Nr.	0	1	2	3	4	5
LDK 10/10	1500008300	6 x 6 x 0.5*	3.7 x 3.7	0.03	1.1	21.75	28.5
LDK 10/25	1500008500	6 x 12 x 0.5*	3.7 x 10	0.05	1.8	21.75	28.5
LDK 20/20	1500008600	10 x 10 x 0.5*	7.7 x 7.7	0.18	2.4	21.75	28.5

Column definitions:

- 0: Size (L x W x H) [inch]
1: Sealing area [inch]
2: Air requirement, at working pressure [cu. ft.]
3: Weight, approx. [lbs]
4: Working pressure [psi]
5: Test pressure [psi]