
Pipe Sealing Bags CR



- good handling (length/weight)
- very flexible applicable
- with integrated hose as an option
- good resistance to oil and chemicals

The oil-resistant alternative to the classics.

The Pipe Sealing Bags of chloroprene rubber (CR) are characterised by an increased resistance to chemicals (e.g. against mineral oils, heating oil etc.) compared to conventional Pipe Sealing Bags of natural rubber (NR).



Technical Data

RDK 2.5 bar - Test counter-pressure 10 m WC (14.5 psi)

RDK 1.5 bar - Test counter-pressure 5 m WC (7.25 psi)

Product	Art.-Nr.	0	1	2	3	4	5	6
RDK 7/15	1 440 008 100	36.25	2.7	1.3	2.8-6	12	13.6	0.5
RDK 10/20	1 440 024 300	36.25	3.5	1.3	4-8	9.8	11.6	0.9
RDK 15/30	1 440 008 000	36.25	5.7	3.1	6-12	13.8	15.6	2.5
RDK 20/40	1 440 027 100	36.25	7.7	7.5	8-16	25.6	27.6	7.9
RDK 30/60	1 440 007 900	36.25	11.6	16.1	12-24	28.9	30.4	18
RDK 60/120	1 480 004 800	21.75	22.8	59.5	24-48	52	53.7	87.4

Column definitions:

- 0: Pressure [psi]
- 1: Diameter approx. [inch]
- 2: Weight [lbs]
- 3: Pipe diameter [inch]
- 4: Cylinder length [inch]
- 5: Total length [inch]
- 6: Air requirement [cu. ft.]