

Mini Test Sealing Bags



- extremely short design
- extremely expandable
- up to 1 bar (14.5 psi) counter-pressure
- optimised handling by valve connection

The small ones with duct.

Mini test sealing bags 2.5 bar can be used for testing, sealing and bypassing with repairs and maintenance work, e.g. sealing tests, channel inspection, maintenance, repair and cleaning.

Technical Data

Standard test counter-pressure of 10 m WC (14.5 psi).

* including valve connection

Product	Art.-Nr.	0	1	2	3	4	5	6	7	8
PDK 4/7	1 441 000 701	36.25	1.6-2.8	6.1	1.5	1 x 4 mm	9.8	0.12	0.9	14.5
PDK 7/10	1 441 043 900	36.25	2.8-4	7.48	2.7	1/2"	13.39	0.2	0.9	14.5
PDK 10/15	1 441 035 400	36.25	4-6	5.9	3.5	1/2"	11,8*	0.07	2.2	14.5
PDK 15/20	1 441 035 200	36.25	6-8	7.7	5.7	1/2"	13,6*	0.42	5.5	14.5
PDK 20/30	1 441 035 300	36.25	8-12	9.8	7.2	1"	16*	0.54	9.9	14.5

Column definitions:

- 0: Pressure [psi]
- 1: Pipe diameter [inch]
- 2: Cylinder length [inch]
- 3: Diameter approx. [inch]
- 4: Opening
- 5: Total length [inch]
- 6: Air requirement [cu. ft.]
- 7: Weight [lbs]
- 8: Test counterpressure [psi]