

Lateral packers



- high flexibility
- sturdy spherical heads
- very good bending characteristics
- increased slipping qualities

The intelligent solution that saves money.

Vetter lateral packers are the ideal solution for pipes with small diameters, especially pipelines in the building lateral area. The flexible construction ensures good slipping qualities, bending characteristics and handling. That facilitates quick application, reducing your working hours. The open safety coupling with a lock pin prevents unwanted decoupling. The spherical heads are vulcanised in.

The lateral packers are available in 2 sizes from 70 - 250 mm (2.7 - 9.8 inch) and lengths up to 3 m (9.8 ft.).

Technical Data

Operating pressure: 2,5 bar (36,25 psi)

Product	Art.-Nr.	0	1	2	3	4	5	6
100-250	1 491 068 700	16.9	118	21.75	107.1	3.9 - 9.8	3.6	113
70-110	1 491 069 200	1.9	24	36.25	17.9	2.8 - 4.3	2	19.5
70-110	1 491 067 800	3.1	39	36.25	31.5	2.8 - 4.3	2	35
70-110	1 491 067 900	3.5	59	36.25	51.2	2.8 - 4.3	2	54.7
70-110	1 491 068 000	4.4	79	36.25	70.9	2.8 - 4.3	2	74.4
70-110	1 491 068 100	5.3	98	36.25	90.6	2.8 - 4.3	2	94.1
70-110	1 491 068 200	6.3	118	36.25	110.2	2.8 - 4.3	2	113.8
100-250	1 491 069 300	3.3	24	21.75	12.6	3.9 - 9.8	3.6	18.5
100-250	1 491 068 300	5.6	39	21.75	28.3	3.9 - 9.8	3.6	34.3
100-250	1 491 068 400	8.4	59	21.75	48	3.9 - 9.8	3.6	53.9
100-250	1 491 068 500	11.2	79	21.75	67.7	3.9 - 9.8	3.6	73.6
100-150	1 491 068 600	14.1	98	21.75	87.4	3.9 - 9.8	3.6	93.3

Column definitions:

- 0: Weight [lbs]
- 1: Length [inch]
- 2: Working pressure [psi]
- 3: Application length (d.max.) [inch]
- 4: Application range [inch]
- 5: Diameter, approx. [inch]
- 6: Application length (d.min.) [inch]