

# Test Sealing Bags



- Lighter than test bag with inner tube
- Only 3 sizes from 100-1,000 mm(4-40 inch)
- Flexible, robust design
- For tests according to DIN EN 1610

The small ones with duct. Mini test sealing bags 2.5 bar can be used for testing, sealing and bypassing with repairs and maintenance work, e.g. sealing tests, channel inspection, maintenance, repair and cleaning.

## Technical Data

- PDK 2.5 bar- test counter pressure of 10mWC (14.5 psi)
- PDK 1.5 bar - test counter-pressure of 5 mWC (7.25 psi)
- PDK 0.5 bar - Test counter pressure 2mWC (2.9 psi)

Product	Art.-Nr.	0	1	2	3	4	5	6	7
PDK 10/15	1441000701	36.25	1.6-2.8	1.5	6.1	0.9	9.8	0.12	1 x 4 mm
PDK 7/15 Flex	1441001201	36.25	2.8-6	2.7	13.8	3.8	15.6	0.5	1 x 1/2" AG
PDK 10/20 Flex	1441018502	36.25	4-8	3.5	12	2.9	13.6	0.53	1 x 1" AG
PDK 15/30 Flex	1441022801	36.25	6-12	5.7	13.8	7.5	15.6	1.6	1 x 2" AG
PDK 20/40 Flex	1441018600	36.25	8-16	7.7	25	19	26.7	7.9	1 x 2" AG
PDK 20/50 Flex	1441031200	36.25	8-20	7.2	29.3	15	31	8.37	1 x 2" AG
PDK 30/60 Flex	1441018701	36.25	12-24	11.6	28.9	24.3	32.1	16.03	1 x 2" AG
PDK 50/100 Flex	1481003501	21.75	20-40	17.7	43.7	59.5	45.6	52.1	1 x 2" AG
PDK 60/120 Flex	1481009501	21.75	24-48	22.8	52	77.2	53.7	85.6	1 x 2" AG
PDK 80/140 Flex	1481024000	21.75	32-56	30.9	71.3	121.3	73	108.5	1 x 2" AG
PDK 140/170 Flex	1401000400	7.25	56-67	53.2	74.8	137.8	84.7	306.1	1 x 2" AG
PDK 170/200 Flex	1401000700	7.25	67-80	63.8	74.8	142.2	90.6	309.8	1 x 2" AG

### Column definitions:

- 0: Pressure [psi]
- 1: Pipe diameter [inch]
- 2: Diameter approx. [inch]
- 3: Cylinder length [inch]
- 4: Weight [lbs]
- 5: Total length [inch]
- 6: Air requirement [cu. ft.]
- 7: Opening