

# Pipe Sealing Bags CR



- good handling (length/weight)
- very flexible applicable
- with integrated hose as an option
- good resistance to oil and chemicals

**The oil-resistant alternative to the classics.**

The Pipe Sealing Bags of chloroprene rubber (CR) are characterised by an increased resistance to chemicals (e.g. against mineral oils, heating oil etc.) compared to conventional Pipe Sealing Bags of natural rubber (NR).

## Technical Data

RDK 2.5 bar - Test counter-pressure 10 m WC (14.5 psi)

RDK 1.5 bar - Test counter-pressure 5 m WC (7.25 psi)

| Product    | Art.-Nr.      | 0     | 1    | 2    | 3     | 4    | 5    | 6    |
|------------|---------------|-------|------|------|-------|------|------|------|
| RDK 7/15   | 1 440 008 100 | 36.25 | 2.7  | 1.3  | 2.8-6 | 12   | 13.6 | 0.5  |
| RDK 10/20  | 1 440 024 300 | 36.25 | 3.5  | 1.3  | 4-8   | 9.8  | 11.6 | 0.9  |
| RDK 15/30  | 1 440 008 000 | 36.25 | 5.7  | 3.1  | 6-12  | 13.8 | 15.6 | 2.5  |
| RDK 20/40  | 1 440 027 100 | 36.25 | 7.7  | 7.5  | 8-16  | 25.6 | 27.6 | 7.9  |
| RDK 30/60  | 1 440 007 900 | 36.25 | 11.6 | 16.1 | 12-24 | 28.9 | 30.4 | 18   |
| RDK 60/120 | 1 480 004 800 | 21.75 | 22.8 | 59.5 | 24-48 | 52   | 53.7 | 87.4 |

### Column definitions:

- 0: Pressure [psi]
- 1: Diameter approx. [inch]
- 2: Weight [lbs]
- 3: Pipe diameter [inch]
- 4: Cylinder length [inch]
- 5: Total length [inch]
- 6: Air requirement [cu. ft.]