

Compact gully sealing bags



- Good resistance to oil and chemicals
- Ready to use in transport case
- Withstands counterpressure of up to 2 m WC (2.9 psi)
- For gullies with diameters up to 80 cm (32 inch)

Reliably seal sewage systems and gullies.

With the Vetter compact gully sealing bag, you can take action immediately. Seal the gully together with the sewer inlet: ready to use on the spot, quick to put into position and easy to handle. The sealing bags withstand counterpressure of up to 2 m water column (2.9 psi) and can be inflated with the supplied compressed air cylinder. Seal gullies with a diameter of up to 80 cm (32 inch) the easy way.

Technical Data

- Working pressure: 0.5 bar (7.25 psi)
- Test pressure: 0.65 bar (9.4 psi)
- Test counterpressure: 2 m water column (2.9 psi)

| Product | Art.-Nr. | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|---------|------------|------|-------|----|------|-----|------|------|-----|-----|
| 30-50 | 1460000101 | 11.6 | 12-20 | 16 | 18.1 | 4.5 | 8.2 | 7.25 | 9.4 | 2.9 |
| 50-80 | 1460001400 | 17.7 | 20-32 | 16 | 18.1 | 15 | 18.3 | 7.25 | 9.4 | 2.9 |

Column definitions:

- 0: Diameter [inch]
- 1: Gully outlet min. - max. [inch]
- 2: Cylinder length [inch]
- 3: Total length [inch]
- 4: Air requirement, at working pressure [cu. ft.]
- 5: Weight, approx. [lbs]
- 6: Working pressure [psi]
- 7: Test pressure [psi]
- 8: Test counterpressure [psi]